



## PATENT ABSTRACTS OF JAPAN

(11) Publication number: **07259778 A**(43) Date of publication of application: **09.10.95**

(51) Int. Cl.

**F04C 29/10**  
**F04C 18/16**
(21) Application number: **06048531**(22) Date of filing: **18.03.94**(71) Applicant: **DAIKIN IND LTD**
 (72) Inventor: **YAMAGUCHI NORIHIDE**  
**OKAMOTO TAMOTSU**  
**SHIBUYA EISAKU**

 (54) **CAPACITY CONTROL DEVICE FOR SCREW  
 COMPRESSOR**

COPYRIGHT: (C)1995,JPO

(57) Abstract:

**PURPOSE:** To ensure a proper control speed in a wide operation range where a differential pressure between high and low pressures is fluctuated and to provide a proper load up speed regardless of a cooling water temperature during starting.

**CONSTITUTION:** When a differential pressure between high and low pressures is low during load up, only an on-off valve SV2 on the low resistance side is opened, and oil is discharged through a first discharge passage 8a on the load up side. When the level differential pressure is high, only an on-off valve SV3 on the high resistance side is opened and oil is discharged through a second discharge passage 8b on the load up side. This constitution improves drainage of oil from a chamber 51 on the load side when the differential pressure is low, prevents the occurrence of defective operation of load up and a delay of load up, and prevents a load up speed from being excessively increased when the differential pressure is high.

